INTERIOR SIGNAGE STANDARDS & ADA INSTALLATION GUIDELINES

- 1 1/4" Acrylic Painted WVU Blue PMS 295/MP29294 Satin
- Tactile Color: White Font: Helvetica Medium
- (3) Grade 2 Braille
- 4 Double Faced Tape

Types of Restroom Signage



WHC-RR



Types of All Gender Restroom and Changing Room Signage

1 **ALL-GENDER** RESTROOM ③

- 1/4" Acrylic Painted WVU Blue PMS 295/ MP29294 Satin
- Tactile Color: White Font: Helvetica Medium
- (3) Grade 2 Braille
- 4 Double Faced Tape



AGHC-CR







AGHC-RR




AGCT-RR

AGHCCT-RR Size: 8" x 8.75"



Types of Bathroom Signage



W-BR

Size: 6" x 8"

**add Handicap symbol to signs when applicable

- 1/4" Acrylic Painted WVU Blue PMS 295/ MP29294 Satin
- Tactile Color: White Font: Helvetica Medium
- (3) Grade 2 Braille
- 4 Double Faced Tape





ALL-GENDER BATHROOM

AG-BR Size: 8" x 8.75"





Size: 8" x 10.25"

Lactation Room Sign


1) 1/4" Acrylic Painted WVU Blue PMS 295/ MP 29294 Satin

(2) Tactile Color: White; Font: Helvetica Medium

(3) Grade 2 Braille

4 Double Faced Tape

West Virginia University.



RR4

Size: 7" x 8"

- 1/4" Acrylic Painted WVU Blue PMS 295/ MP 29294 Satin
- (2) Tactile Color: White; Font: Helvetica Medium
- (3) Grade 2 Braille
- (4) Double Faced Tape


RR4- Location Indicator Sign


LACTATION
ROOM
LOCATED ON
THE ???
FLOOR

ALL GENDER
RESTROOM
LOCATED ON ???
FLOOR
LACTATION ROOM
LOCATED ON ???
FLOOR

Note: For All Gender restroom or Lactation room in the building








T1 and T2 - Room Signs


- 1/4" Acrylic Painted WVU Blue PMS 295/ MP 29294 Satin
- (2) Tactile Color: White Font: Helvetica Medium
- (3) Grade 2 Braille
- (4) Double Faced Tape



T3- Room ID with Name








- 1/8" Acrylic Painted WVU Blue PMS 295/ MP 29294 Satin
- ② Tactile Color: White; Font: Helvetica Medium
- (3) Grade 2 Braille
- 4 Double Faced Tape
- (5) Window for name (8.5"x11"); 1/8" spacer Tape/ Non-Glare Acrylic
- Window for schedule/ office hours (8.5"x11") 1/8" spacer Tape/ Non-Glare Acrylic
- Backplate 1/8" PVC painted WVU Blue PMS 295/ MP 29294 Satin with Two sets of Thumbholes on backplate for both window, Paint both sides

T3A – Room ID with name and paper insert

Size: 8 1/2" X 16.625"






- (1) 1/8" Acrylic Painted WVU Blue PMS 295/ MP 29294 Satin
- (2) Tactile Color: White; Font: Helvetica Medium
- (3) Grade 2 Braille
- 4 Double Faced Tape
- (5) Window for name/schedule (8.5"x11"); 1/8" spacer Tape/ Non-Glare Acrylic
- 6 Backplate 1/8" PVC painted WVU Blue PMS 295/ MP 29294 Satin with Two sets of Thumbholes on backplate for window, Paint both sides


T3A - Room ID without name insert



T3B – Room ID with Name Insert (2) Slot



West Virginia University.




- 1) 1/8" Acrylic Painted WVU Blue PMS 295/ MP 29294 Satin
- (2) Tactile Color: White Font: Helvetica Medium
- 3) Grade 2 Braille
- (4) Double Faced Tape
- Window for suite name/ list of names in suite (11"x17") 1/8" Spacer Tape/Non-Glare Acrylic
- 6 Backplate 1/8" PVC painted WVU Blue PMS 295/ MP 29294 Satin with Two sets of Thumbholes on backplate for window, Paint both sides

T3C - Room ID with 11"x17" Insert Slot



T3D - Name ID Add On



1/8" Clear Acrylic
Faceplate Top/ Bottom
border painted WVU Blue
PMS 295/MP 29294 Satin

Backplate 1/8" Acrylic

- painted
 WVU Blue PMS 295/ MP
 29294 Satin with
 Thumbholes on Back
 Painted both sides
- (3) Double Faced Tape



MAXIMUM OCCUPANCY **NOT TO EXCEED TBD PERSONS** BY ORDER OF STATE FIRE MARSHAL

T4

Size: 8" X 6"

T4 – Maximum Occupancy Sign (Required by WV State Fire Code)

- Dibond Print Direct, Brushed
 Silver Horizontal Grain Rounded
 Corners white spot
- 2 Red and Black Lettering
- 3 Double Faced Tape

Note: Maximum Occupancy Signs shall be posted in rooms where required by WV State Fire Code.

- Every room constituting an assembly occupancy and not having fixed seats shall have the occupant load of the room posted in a conspicuous place near the main exit from the room.
- If a room with an occupant load calculated of more than 50 persons yet the room only has one door, a sign shall be placed in that room stating "Maximum Occupancy 49 Persons" shall be posted. The occupancy limit shall be calculated by the architect in the accordance with the WV State Fire Code.







- ① ¼" acrylic painted Red
- 2) Rowmark; white
- 3 Grade 2 Braille
- 4 Double Faced Tape

Emergency Exit Size: 8" X 12"

Fire Door Keep Closed
Size: 9" X 3"

Fire Door

Keep Closed

2"

Action to be seen as a seen as

Emergency Exit/ Fire Door Keep Closed Signage for (Stairwell Doors)





Surface Mount or 3/8" hole (two-top and bottom center)

White lettering, 6" Tall with 1" thickness

0.063" Engineering grade Reflection Aluminum

FDC

Size: 12" X 18"

Fire Department Connection (Exterior signage)




SPRINKLER CONTROL SYSTEM

ELEVATOR EQUIPMENT ROOM

Sprinkler Control Room & Elevator Equipment Room

install below room number

For Fire Department Notification





Size: 6" X 8"





1 4" Acrylic painted WVU Blue PMS 295/ MP 29294 Satin

Tactile Color: White Font: Helvetica Medium

(3) Grade 2 Braille

(4) Double Faced Tape


T6 - Sign Example next to Elevator – option 1

4)

West Virginia University.

T6

Size: 9" X 9"



- 1 1/2" Acrylic painted WVU Blue PMS 295/ MP 29294 Satin
- Tactile Color: White Font: Helvetica Medium
- 3 Grade 2 Braille
- 4 Double Faced Tape


THIS SIGN CAN BE USED FOR ADDITIONAL INFORMATION IN A STAIRWELL BUT NOT THE ONLY SIGN. SW4 HAS TO BE POSTED.

T7 - Level or Floor Sign

T7
Size: 6" X 8"




T8 - Confined Space Sign



T8

Size: 8 1/2" X 3"





1/4" Acrylic painted WVU Blue PMS 295/ MP 29294 Satin

Tactile Color: White Font: Helvetica Medium

(3) Grade 2 Braille

4

4 Double Faced Tape

ON THIS SIGN, STAIR NUMBER AND LEVEL COULD BE ADDED TO THIS SIGN POSTED ON THE FLOOR SIDE.

SW - Stair Signage

SW

Size: 7" X 8"





1/4" Acrylic painted

WVU Blue PMS 295/ MP 29294 Satin

Tactile Color: White Font: Helvetica Medium

(3) Grade 2 Braille

(4) Double Faced Tape


SW2 - Sign Example next to Elevator option 2

SW2

Size: 1'-1 1/2" X 10 1/4"



SW3 - Stairwell Door EXIT signage





STAIR 3

FLOOR 1 FOR EXIT

FLOOR
FLOOR B THRU 2

SW4 – Stairwell Signage

STAIR 3

2 FLOOR

OOR B THRU

FLOOR B THRU 2 FLOOR 1 FOR EXIT

SW4

Size: 13" X 15"


Note if there is Roof Access from the stairwell, add additional note to the sign. (1) ¼" Acrylic painted WVU Blue PMS 295/ MP 29294 Satin

(2) Tactile Color: White; Font: Helvetica Medium

- (3) Double Faced Tape
- (4) Grade 2 Braille








Printed Brushed Di-Bond with rounded corners. Text
Color WVU Blue, clear coat, and 2 Faced Tape
If Exterior install – may need to screw to wall.


Note: Extra sign might be needed per where deliveries or something that needs to be clear to visitor or information for building.


Informational Sign (special case)

Size is determined on content for sign










Size: 17.5" x 11.5" Inserts: 11" x 17"





Luminescent Backer (special insert)



WEST VIRGINIA UNIVERSITY CAMPUS

BUILDING DIRECTORIES & DEPARTMENT ENTRANCE SIGNS

11" EVANSDALE 1.25" (1) 6" **LIBRARY** 2 ③ 4 (5) Directory 18" 17" 7 Insert 1 6 11" (8) 6" 1 Panel Size: 11"x30"

Building Directory – D1 and D2

4


- 1 Acrylic Painted WVU Blue PMS 295- MP 29294 Satin
- 2 Tactile Rowmark Color: White Font: Helvetica Medium
- 3 Backplate 1/8" Dibond
- 4 4 Double Faced Tape
- (5) 2" Magnetic Strip (5) Strips Total
- 6 Faceplate 1/8" Non-glare Acrylic Paint on 2nd Surface
- Cold Rolled Metal
 (to attach to Magnet)
- 8 Backplate 1/8" Acrylic Painted WVU Blue PMS 295/ MP 29294 Satin



2 Panel

Size: 22"x30"






Size: 33"x30"



Building Directory – D4




4 Panel

Size: 44"x30"



Department Name Sign



DNS- Department Name Sign

Size: may vary depending on location



ADA SIGN INSTALLATIONS & GUIDELINES

FAQ and Tips

The ADA (Americans with Disabilities Act) helps remove barriers for people with disabilities. More than 2.5 million Americans suffer from visual impairment-not just blindness. High contrast ADA compliant signs help ensure accessibility for seniors, the visually impaired and blind. An ADA compliant sign is required for every permanent room or space in a building. This document is designed to help you understand how ADA compliant signs should be installed. Always defer to your local building authority for regulations and code updates You can review the guidelines enforceable as of March 15, 2016 at www. ada.gov. Chapter 7, section 703 of the ADA code relates to signs.

FREQUENTLY ASKED QUESTIONS

Q: Do all signs need to be ADA compliant and have Braille and tactile letters?

A: No, there are a number of signs that are not required to be ADA compliant. Building addresses, directories, parking signs and temporary signs don't need to be ADA compliant. Temporary signs are those used for 7 days or less.


Q: Do I need ADA compliant signs in the stairwells of my building? **A:** You are required to have tactile sign next to each door inside the stairwell. These signs should identify the floor level, stair level and exit level. Some local fire codes have size requirements for those signs. You should check with your local code authority.

INSTALLATION TIPS

- Although signs can be installed at varying heights, we suggest installing all your signs at 54" from floor to the center of the sign.
- Install signs with double sided tape by removing the tape backing.
 Then place the sign on a level and press it firmly in place against the wall.
- Clear silicone should be added to the back of heavy or oversized signs.



Mounting Heights



- The baseline of the tactile copy can be mounted between 48" at the lowest point to 60" at the highest point. This allows signs of different sizes to be mounted on the same visual plane.
- Elevator cars are excluded from this rule.




Mounting Options

Signs should be mounted to the wall on the latch side of the door. If there is no room on that wall, the sign may be mounted on the nearest adjacent wall.



In the case of outward swinging doors, the sign must be mounted to the wall outside of the arc of the door swing. The sign should be located within an 18"x18" square of clear floor space (18" away from the door and 18" away from the wall). See Diagram.





Double Door: (one active leaf): Sign shall be located on inactive leaf.



Inward swinging doors: Sign may be mounted on door if three criteria are met: !) the door closes automatically, 2) the sign is mounted on the push side of the door, 3) the door does not have a hold-open device. (Common examples of doors that meet these criteria are kitchen doors, restroom doors, etc.).




Single Door: sign shall be mounted next to door on the latch side.



Double Door: (two active leaves): Sign shall be located to the right of right handed door.



Overhead Signs and Projection Signs



PROJECTING SIGN

- The bottom of overhead signage must be 80" above the floor.
- Projecting wall mounted signs must be a minimum of 27" off the floor and have a maximum protrusion of 4" into a pathway.
- Signs should not interfere with or block any door function, emergency equipment or sprinklers.

